

Wynn's Hydraulic Systems Concentrate

Autoserv NZ Ltd

Chemwatch: **52904**Version No: **5.1.1.1**

Safety Data Sheet according to HSNO Regulations

Chemwatch Hazard Alert Code:

Issue Date: **27/06/2017**Print Date: **13/08/2017**S.GHS.NZL.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Wynn's Hydraulic Systems Concentrate
Synonyms	mineral hydraulic lubricant, 58701A 5 litres/58720 20 litres
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified	Lubricating oil for hydraulic systems.
uses	Lubilicating oil for Hydraulic Systems.

Details of the supplier of the safety data sheet

Registered company name	Autoserv NZ Ltd	ITW AAMTech Australia
Address	Unit 2/38 Trugood Drv, East Tamaki AUCK 2013 New Zealand	1-9 Nina Link, Dandenong South VIC 3175 Australia
Telephone	0800 438 996	1800 177 989
Fax	09 272 1949	1800 308 556
Website	www.autoserv.co.nz	www.aamtech.com.au
Email	warehouse@autoserv.co.nz	info@aamtech.com.au

Emergency telephone number

Association / Organisation	Not Available	Not Available
Emergency telephone numbers	0800 2436 2255	1800 039 008
Other emergency telephone numbers	0800 764 766	0800 2436 2255

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Not regulated for transport of Dangerous Goods.

Classification ^[1]	Acute Toxicity (Oral) Category 5, Acute Toxicity (Dermal) Category 5, Acute Toxicity (Inhalation) Category 5, Skin Corrosion/Irritation Category 3, Eye Irritation Category 2B, Specific target organ toxicity - single exposure Category 3 (narcotic effects)
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	6.1E (dermal), 6.1E (inhalation), 6.1E (oral), 6.3B, 6.4A (mild), 6.9 (narcotic)

Label elements

Issue Date: **27/06/2017**Print Date: **13/08/2017**

Hazard pictogram(s)



SIGNAL WORD

WARNING

Hazard statement(s)

H303	May be harmful if swallowed.
H313	May be harmful in contact with skin
H333	May be harmful if inhaled
H316	Causes mild skin irritation
H320	Causes eye irritation.
H336	May cause drowsiness or dizziness.

Precautionary statement(s) Prevention

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P271	Use only outdoors or in a well-ventilated area.

Precautionary statement(s) Response

P304+P312	IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.

Precautionary statement(s) Storage

		1 (17)
	P405	Store locked up.
	P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501 Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
64741-96-4.	>60	naphthenic distillate, heavy, solvent-refined (severe)
Not Available	10-30	other non-hazardous ingredients

SECTION 4 FIRST AID MEASURES

NZ Poisons Centre 0800 POISON (0800 764 766) | NZ Emergency Services: 111

Description of first aid measures

If this product comes in contact with the eyes:

Eye Contact

- Wash out immediately with fresh running water.
 Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- ▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

Chemwatch: 52904 Page 3 of 9 Issue Date: 27/06/2017 Version No: 5.1.1.1 Print Date: 13/08/2017

Wynn's Hydraulic Systems Concentrate

Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

- ▶ Heavy and persistent skin contamination over many years may lead to dysplastic changes. Pre-existing skin disorders may be aggravated by exposure to this product.
- ▶ In general, emesis induction is unnecessary with high viscosity, low volatility products, i.e. most oils and greases.
- ▶ High pressure accidental injection through the skin should be assessed for possible incision, irrigation and/or debridement.

NOTE: Injuries may not seem serious at first, but within a few hours tissue may become swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Product may be forced through considerable distances along tissue planes.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as i result		 Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
	Advice for firefighters	3
		 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves.
	Fire Fighting	► Prevent, by any means available, spillage from entering drains or water course.

- Use water delivered as a fine spray to control fire and cool adjacent area.

Combustible.

- ▶ Slight fire hazard when exposed to heat or flame.
- ▶ Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).

Combustion products include:

Fire/Explosion Hazard

carbon dioxide (CO2)

other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

CARE: Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns. Foaming may cause overflow of containers and may result in possible fire.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills

Slippery when spilt.

- ► Remove all ignition sources.
- ▶ Clean up all spills immediately.

Wynn's Hydraulic Systems Concentrate

Issue Date: **27/06/2017**Print Date: **13/08/2017**

	 Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment.
	Slippery when spilt. Moderate hazard.
Major Spills	▶ Clear area of personnel and move upwind.
	▶ Alert Fire Brigade and tell them location and nature of hazard.
	▶ Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling Prevent concentration in hollows and sumps. Other information Avoid all personal contact, including inhalation. Prevent cocurs area. Prevent concentration in hollows and sumps. Store in original containers. Keep containers securely sealed. No smoking, naked lights or ignition sources. Store in a cool, dry, well-ventilated area.

Conditions for safe storage, including any incompatibilities

Suitable container	 Metal can or drum Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	CARE: Water in contact with heated material may cause foaming or a steam explosion with possible severe burns from wide scattering of hot material. Resultant overflow of containers may result in fire. • Avoid reaction with oxidising agents

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	naphthenic distillate, heavy, solvent-refined (severe)	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	(om) - Sampled by a method that does not collect vapour.

EMERGENCY LIMITS

Ingredient	Material name	IEEL-1	IEEL-2	TEEL-3
Wynn's Hydraulic Systems Concentrate	Not Available	Not Available	Not Available	Not Available
Ingredient	Original IDLH		Revised IDLH	
naphthenic distillate, heavy, solvent-refined (severe)	Not Available		Not Available	
other non-hazardous ingredients	Not Available		Not Available	

Exposure controls

	Casing spines controls are used to account a place of bound by the control of the bound Well decisioned
	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed
	engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to
A	provide this high level of protection.
Appropriate	The basic types of engineering controls are:
engineering controls	Process controls which involve changing the way a job activity or process is done to reduce the risk


Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Chemwatch: **52904**Version No: **5.1.1.1**

Wynn's Hydraulic Systems Concentrate

Issue Date: **27/06/2017**Print Date: **13/08/2017**



Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Clear light brown liquid with mild petroleum odour; does not mix with water.					
Physical state	Liquid	Relative density (Water = 1)	0.929 @15C			
Odour	Not Available	Partition coefficient n-octanol / water	Not Available			
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not available.			
pH (as supplied)	Not Applicable	Decomposition temperature	Not available.			
Melting point / freezing point (°C)	-29 C	Viscosity (cSt)	32.7			
Initial boiling point and boiling range (°C)	>210	Molecular weight (g/mol)	Not Available			
Flash point (°C)	138 (COC)	Taste	Not Available			
Evaporation rate	Not Available	Explosive properties	Not Available			
Flammability	Not Applicable	Oxidising properties	Not Available			
Upper Explosive Limit (%)	Not available.	Surface Tension (dyn/cm or mN/m)	Not Available			
Lower Explosive Limit (%)	Not available.	Volatile Component (%vol)	Not Available			
Vapour pressure (kPa)	Negligible	Gas group	Not Available			
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Applicable			
Vapour density (Air = 1)	>1	VOC g/L	Not Available			

Issue Date: **27/06/2017**Print Date: **13/08/2017**

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information	on toxico	logical	effects

information on toxico	
Inhaled	There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo. Inhaling high concentrations of mixed hydrocarbons can cause narcosis, with nausea, vomiting and lightheadedness. Low molecular weight (C2-C12) hydrocarbons can irritate mucous membranes and cause incoordination, giddiness, nausea, vertigo, confusion, headache, appetite loss, drowsiness, tremors and stupor.
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual. Ingestion of petroleum hydrocarbons can irritate the pharynx, oesophagus, stomach and small intestine, and cause swellings and ulcers of the mucous. Symptoms include a burning mouth and throat; larger amounts can cause nausea and vomiting, narcosis, weakness, dizziness, slow and shallow breathing, abdominal swelling, unconsciousness and convulsions.
Skin Contact	There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Skin contact with the material may damage the health of the individual; systemic effects may result following absorption. Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.
Eye	There is some evidence to suggest that this material can cause eye irritation and damage in some persons. Direct eye contact with petroleum hydrocarbons can be painful, and the corneal epithelium may be temporarily damaged. Aromatic species can cause irritation and excessive tear secretion.
Chronic	Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin. Oil may contact the skin or be inhaled. Extended exposure can lead to eczema, inflammation of hair follicles, pigmentation of the face and warts on the soles of the feet.

Wynn's Hydraulic	тохісіту	IRRITATION
Systems Concentrate	Not Available	Not Available
	тохісіту	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Not Available
	Inhalation (rat) LC50: >3.9 mg/l/4hr ^[1]	
	Inhalation (rat) LC50: >4.7 mg/l/4hr ^[1]	
nanhthanic distillata	Inhalation (rat) LC50: >5 mg/l/4hr ^[1]	
naphthenic distillate, heavy, solvent-refined	Inhalation (rat) LC50: >5.2 mg/l/4hr ^[1]	
(severe)	Inhalation (rat) LC50: >5.3 mg/l/4hr ^[1]	
	Inhalation (rat) LC50: 10.5 mg/l/4hr ^[1]	
	Inhalation (rat) LC50: 5.7 mg/l/4hr ^[1]	
	Inhalation (rat) LC50: 9.6 mg/l/4hr ^[1]	
	Oral (rat) LD50: >2000 mg/kg ^[1]	
Legend:	·	bstances - Acute toxicity 2.* Value obtained from manufacturer's SDS. ECS - Register of Toxic Effect of chemical Substances

Chemwatch: 52904 Page 7 of 9 Issue Date: 27/06/2017 Version No: 5.1.1.1

Wynn's Hydraulic Systems Concentrate

Print Date: 13/08/2017

The materials included in the Lubricating Base Oils category are related from both process and physical-chemical perspectives:

The potential toxicity of a specific distillate base oil is inversely related to the severity or extent of processing the oil has undergone, since:

- The adverse effects of these materials are associated with undesirable components, and
- The levels of the undesirable components are inversely related to the degree of processing;
- Distillate base oils receiving the same degree or extent of processing will have similar toxicities;
- The potential toxicity of residual base oils is independent of the degree of processing the oil receives.
- The reproductive and developmental toxicity of the distillate base oils is inversely related to the degree of processing.

Unrefined & mildly refined distillate base oils contain the highest levels of undesirable components, have the largest variation of hydrocarbon molecules and have shown the highest potential cancer-causing and mutation-causing activities. Highly and severely refined distillate base oils are produced from unrefined and mildly refined oils by removing or transforming undesirable components.

For highly and severely refined distillate base oils:

In animal studies, the acute, oral, semilethal dose is >5g/kg body weight and the semilethal dose by skin contact is >2g/kg body weight. The semilethal concentration for inhalation is 2.18 to >4 mg/L. The materials have varied from "non-irritating" to "moderately irritating" when tested for skin and eye irritation. Testing for sensitisation has been negative.

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

Wynn's Hydraulic **Systems Concentrate** & NAPHTHENIC DISTILLATE, HEAVY, **SOLVENT-REFINED** (SEVERE)

NAPHTHENIC

(SEVERE)

DISTILLATE, HEAVY,

SOLVENT-REFINED

No significant acute toxicological data identified in literature search.

Acute Toxicity	~	Carcinogenicity	0
Skin Irritation/Corrosion	~	Reproductivity	0
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0
Mutagenicity	0	Aspiration Hazard	0

Legend:

★ - Data available but does not fill the criteria for classification

✓ – Data available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Wynn's Hydraulic Systems Concentrate	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE		
	Not Available	Not Available	Not Available	Not Available	Not Available		
naphthenic distillate,	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE		
heavy, solvent-refined (severe)	EC50	48	Crustacea	>1000mg/L	1		
(Severe)	NOEC	504	Crustacea	>1mg/L	1		
Legend:	Toxicity 3. EP	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentratic					

DO NOT discharge into sewer or waterways.

Data 8. Vendor Data

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Wynn's Hydraulic Systems Concentrate

Issue Date: **27/06/2017**Print Date: **13/08/2017**

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging

disposal

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
 - Recycle wherever possible or consult manufacturer for recycling options.
 - ► Consult State Land Waste Authority for disposal.
 - Bury or incinerate residue at an approved site.
 - Recycle containers if possible, or dispose of in an authorised landfill.

Ensure that the disposal of material is carried out in accordance with Hazardous Substances (Disposal) Regulations 2001.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002624	Not otherwise specified(subsidiary hazard)

NAPHTHENIC DISTILLATE, HEAVY, SOLVENT-REFINED (SEVERE)(64741-96-4.) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified

New Zealand Workplace Exposure Standards (WES)

by the IARC Monographs

New Zealand Inventory of Chemicals (NZIoC)

Location Test Certificate

Subject to Regulation 55 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations, a location test certificate is required when quantity greater than or equal to those indicated below are present.

Hazard Class	Quantity beyond which controls apply for closed containers	Quantity beyond which controls apply when use occurring in open containers
Not Applicable	Not Applicable	Not Applicable

Approved Handler

Subject to Regulation 56 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations and Regulation 9 of the Hazardous Substances (Classes 6, 8, and 9 Controls) Regulations, the substance must be under the personal control of an Approved Handler when present in a quantity greater than or

Chemwatch: 52904 Page 9 of 9 Issue Date: 27/06/2017 Version No: 5.1.1.1

Wynn's Hydraulic Systems Concentrate

Print Date: 13/08/2017

equal to those indicated below.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Tracking Requirements

Not Applicable

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	N (naphthenic distillate, heavy, solvent-refined (severe))
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	N (naphthenic distillate, heavy, solvent-refined (severe))
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.